MADRIX USB Contact Closure

MADRIX I/O products are supplementary input and output devices for the MADRIX software

Art. No.: 51860382

GTIN: 4260263421110

The article is no longer in our assortment.

Features:

- External equipment, such as sensors, bring additional automation processes and interaction to any LED project using MADRIX software
- This digital input device registers if its circuit is either open or closed. In most cases, it is used to build a switch or trigger
- Incoming values are directly translated into DMX data in the MADRIX software
- MADRIX I/O requires MADRIX 3. Please update at least to MADRIX 3.4
- More information available at www.madrix.com
- The device can be connected via USB to the PC in connection with MADRIX software
- Made in Germany

Technical specifications:

Power supply:	5 V DC 500 mA
IP classification:	IP30
Power connection:	Fixed power supply cord for USB A mains connection
USB port:	USB 2.0, Typ B
PC connect:	MADRIX software via USB
Dimensions:	Width: 3 cm Depth: 4,4 cm Height: 2,3 cm

Logistic

EAN / GTIN: 4260263421110

Weight: 0,07 kg

Length: 0.18 m

Width: 0.11 m

Heigth: 0.03 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	60 g

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.