

# **MADRIX USB Contact Closure**

MADRIX I/O products are supplementary input and output devices for the MADRIX software

Art. No.: 51860382 GTIN: 4260263421110



# The article is no longer in our assortment.

#### Features:

- They enable additional automation and interaction for LED projects.
- MADRIX USB Contact Closer is a digital input device that registers whether the circuit is open or closed. It is mainly used as an on/off switch
- Incoming values are directly translated into DMX data in the MADRIX software
- MADRIX I/O requires MADRIX 3. Please update at least to MADRIX 3.4
- More information available at www.madrix.com
- The device can be connected via USB to the PC in connection with MADRIX software
- Made in Germany

## **Technical specifications:**

Power supply:	5V DC 500 mA
IP classification:	IP30
Power connection:	Fixed power supply cord for USB A mains connection
USB port:	USB 2.0, type B
PC connect:	MADRIX software via USB
Dimensions:	Width: 3 cm
	Depth: 4,4 cm
	Height: 2,3 cm
Weight:	0,06 kg

### Logistic

EAN / GTIN: 4260263421110 Weight: 0,07 kg Length: 0.18 m Width: 0.11 m Heigth: 0.03 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.