Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

MADRIX Aura 8

Advanced lighting-control recorder and stand-alone playback unit for 4096 channels

The article is no longer in our assortment.

Features:

- Can transmit up to 4096 DMX channels
- The device is cooled by passive convection cooling -
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; stage; restaurants, bars and hotels; architecture
- For further information about this product, please refer to the Data Sheet under "Downloads" -

Technical specifications:

Power supply:	5-24V DC 300 mA
Power consumption:	1,5 W
IP classification:	IP20
Power connection:	Mains input via special connector recessed mounting
	Mains input via USB, type B
DMX channels:	Output 4096
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version, 10/100/1000 Mbit/s
	Protocol: Streaming ACN (sACN / ANSI E1.31) via 2x RJ-45 (F) mounting version, 10/100/1000 Mbit/s
Cooling:	Passive convection cooling











Logistic





Art. No.: 51860392

GTIN: 4260263421257

Connections:	Network connection via 2 x RJ-45 (F) mounting version
USB port:	Туре В
Weight:	0,24 kg