eurolite®

EUROLITE LED IP T500 6000K 15x1W 15°

Brilliant outdoor floodlight with LED technology, 6000 K







The article is no longer in our assortment.

Features:

- Ideal LED-beam-lighting for permanent installation (recommended) as well as outdoor use
- The weather-resistant housing also allows operation during bad weather
- Extremely compact housing in a beautiful design
- Available in 2 sizes and 2 color temperatures of the white LEDs
- Beam angle 15°
- Floor or ceiling installation possible
- Mounting brackets for installation included
- Ready for connection via power cord with safety plug

Logistic

EAN / GTIN: 4026397425451 Weight: 2,95 kg Length: 0.59 m Width: 0.15 m Heigth: 0.16 m

Technical specifications:

| Power supply: | 230 V AC, 50 Hz |
|------------------------|--|
| Power consumption: | 35 W |
| IP classification: | IP65 |
| Beam angle (1/2 peak): | 15° |
| Color: | White |
| Dimensions: | Width: 50 cm Depth: 8 cm Height: 10 cm |
| Weight: | 2,65 kg |
| Protection grade: | IP65 |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| LED type: | 1 W |
|-------------------------|--|
| LED number: | 15 |
| Beam angle: | 15° |
| Color temperature: | 6000 K |
| Dimensions (L x W x H): | 500 x 80 x 100 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |