

## **EUROLITE LED PAR-56 HCL Short bl**

PAR-56 spot with 9 x 10 W 6in1 LED and RGBAW+UV color mixing

**Art. No.: 51913591** GTIN: 4026397592245











**List price: 224.91 €** 

incl. 19% VAT.

# Features:

- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6;
  LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Party room; Stage; restaurants, bars and hotels
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

#### **Technical specifications:**

| Power supply:      | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 75 W                   |
| IP classification: | IP20                   |

### Logistic

EAN / GTIN: 4026397592245

Weight: 2,09 kg Length: 0.21 m Width: 0.21 m Heigth: 0.28 m

| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  |
|-------------------------|---|
| Fuse:                   | 5 x 20 mm, F 1 A Fuse replaceable   |
| Lamp type:              | LED lamp  |
| LED:                    | 9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)  |
| DMX channels:           | 4; 6; 10  |
| DMX input:              | 3-pin XLR (M) mounting version  |
| DMX output:             | 3-pin XLR (F) mounting version  |
| Cooling:                | 1 x low-noise cooling fan   |
| Control:                | Stand-alone; DMX; Sound to light via Microphone; IR remote control  |
| Preprogrammed in:       | Light'J; LED PC-Control 512; EASY SHOW 1;<br>LED EASY OPERATOR 4x6; LED EASY<br>OPERATOR DELUXE; Light Captain; EASY<br>SHOW 2; EASY SHOW 3 |
| Projection:             | Flicker-free  |
| Beam angle:             | 20°   |
| Beam angle (1/2 peak):  | 20°   |
| Beam angle (1/10 peak): | 38°   |
| Housing color:          | Black   |
| Attachment system:      | Mounting bracket  |
| Display type:           | 4 digit 7-segment LED display   |
| Dimensions:             | Width: 20,5 cm<br>Depth: 17,5 cm<br>Height: 23 cm   |
| Weight:                 | 1,79 kg   |
| Photobiological safety: | Risk Group 0  |
| Remote control          |   |
| Battery:                | 1 x Button cell 3.0 V CR2025 lithium manganese built-in   |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |
|                         |   |