eurolite®

EUROLITE LED ML-56 6000K 25° spot,black

Brilliant LED spotlight in proven Multi Lens design

Art. No.: 51913655

GTIN: 4026397308549

The article is no longer in our assortment.

Features:

- DMX512 control via regular DMX controller (occupies 2 channels)
- Sound-control via built-in microphone
- Sensivity-control via rotary rotary-control
- Master/Slave-mode
- Black housing with attachment eyelet
- Locking possibility at the mounting bracket
- LED illumination angle approximately 25°
- 6000 K color temperature
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Perfect in public places, main halls, stages, lounges and exibitions

Logistic

EAN / GTIN: 4026397308549
Weight: 6,40 kg
Length: 0.29 m
Width: 0.29 m
Heigth: 0.38 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	50,00 W
Dimensions:	Width: 26,5 cm Depth: 29 cm Height: 26,5 cm
LED number:	24
Dimensions (L x W x H):	265 x 265 x 290 mm
Weight:	5 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.