

EUROLITE LED ML-56 HCL 12x10W Floor sil

ML spot with 12 x 10 W 6in1 LED and RGBAW&UV color mixing

Art. No.: 51913678

GTIN: 4026397564716



The article is no longer in our assortment.

Features:

- Equipped with 12 x 6in1 HCL LED in the colors red, green, blue, amber, white and UV
- HSV, 3, 4, 6, 7, 8 or 12 DMX channels selectable
- Functions: RGBAW+UV color mixture, automatic color change, internal programs and user defined auto programs, user defined color presets, dimmer, strobe settings, power limitation, white balance
- Dimmer speed (step response) adjustable
- Sound-control via built-in microphone
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Beam angle 25°
- Addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Optional color filter frame and barndoors available
- Ready for connection with power cord and safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or in black
- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1
- Flicker-free
- With a beam angle of 25°

Logistic

EAN / GTIN: 4026397564716

Weight: 4,10 kg

Length: 0.25 m

Width: 0.25 m

Height: 0.37 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	105 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	1 - 17 Hz
DMX channels:	3 (HSV hue/saturation/value); 3; 4; 6; 7; 8; 12
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1
Projection:	Flicker-free
Beam angle:	25°
Beam angle (1/2 peak):	25°
Beam angle (1/10 peak):	51°
Housing color:	Silver
Dimensions:	Width: 29,5 cm Depth: 25 cm Height: 30 cm
Weight:	3,65 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting