# eurolite®

## EUROLITE LED ML-56 RGB 36x3W bk

PRO LED spotlight in multi lens design



## The article is no longer in our assortment.

#### Features:

- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller (occupies 5 channels)
- 3 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Functions: Static colors, RGB color blend, 6 internal programs, microphone sensitivity, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 36 3 W LEDs
- Beam angle approximately 15°
- Locking possibility at the mounting bracket
- Ready for connection via power cord with safety-plug
- Standing or hanging installation possible
- Silver or black housing available
- 36 powerful LEDs 3 W
- Control via stand-alone; DMX

### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	100,00 W
IP classification:	IP20
Lamp type:	LED lamp

#### Logistic

EAN / GTIN: 4026397481532 Weight: 3,10 kg Length: 0.27 m Width: 0.27 m Heigth: 0.39 m

Art. No.: 51913682 GTIN: 4026397481532







Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

LED type:	36 x 3 W
Control:	Stand-alone; DMX
Beam angle (1/2 peak):	15°
Housing color:	Black
Dimensions:	Width: 25,5 cm
	Depth: 31,5 cm
	Height: 31 cm
Weight:	2,55 kg
DMX channels:	3/5
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	3 W
LED number:	36 (12R, 12G, 12B)
Beam angle:	15°
Dimensions (L x W x H):	255 x 315 x 310 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting