

EUROLITE LED FLD-144 UV 10mm Flood

LED UV floodlight, incl. IR remote control

Art. No.: 51913861

GTIN: 4026397647617



The article is no longer in our assortment.

Features:

- 144 x 10 mm UV LED for dynamic strobe effects and blacklight
- Built-in auto and music show programs
- UV, dimmer and strobe effects
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Swivel mounting bracket
- Additional bracket for floor use
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 144 powerful LEDs 10 mm ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; LED PC-Control 512
- With a beam angle of 20°

Package contents

- 1 x remote control

Logistic

EAN / GTIN: 4026397647617

Weight: 2,70 kg

Length: 0.36 m

Width: 0.13 m

Height: 0.27 m

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 17 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED: | 144 x 10 mm ultra violet (UV) |
| DMX channels: | 1; 2; 2; 3 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light´J; LED PC-Control 512 |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | 20° |
| Beam angle (1/10 peak): | 35° |
| Housing color: | Black |
| Dimensions: | Width: 34,5 cm Depth: 8,5 cm Height: 22 cm |
| Weight: | 2,40 kg |
| Photobiological safety: | Risk Group 0 |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |