EUROLITE LED PIX-24 RGB 24x3W Floodlight

LED floodlight with 30° beam angle

eurolite









The article is no longer in our assortment.

Features:

- Equipped with 24 x 3 W LED (red: 8, green: 8, blue: 8) distributed in 8 segments
- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller
- 6, 9, 15, 24, 27 DMX channels selectable for various applications
- Sound-control via built-in microphone
- Functions: static colors; automatic color change, 14 built-in programs and strobe effect with variable speed; Master/Slave
- On-board control with 2 x 8-digit LC display
- Locking possibility at the mounting bracket
- Available in flood or bar format
- Ready for connection with power cord and safety plug
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Control via Sound to light via Microphone

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	170 W
IP classification:	IP20
DMX channels:	6
Control:	Sound to light via Microphone

Logistic

EAN / GTIN: 4026397388985 Weight: 5,90 kg Length: 0.49 m Width: 0.27 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Beam angle (1/2 peak):	30°
Dimensions:	Width: 44,5 cm
	Depth: 11,5 cm
	Height: 16 cm
Weight:	5,50 kg
DMX channels:	6, 9, 15, 24, 27
DMX connection:	3-pin XLR
LED number:	24
LED type:	3 W
Beam angle:	30°
Dimensions (L x W x H):	445 x 150 x 195 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting