eurolite®

EUROLITE LED CLS-20 HCL Flood Light

LED flood light with RGBWA+UV LEDs (6in1)











The article is no longer in our assortment.

Features:

- Equipped with 18 x 6in1 hexacolor LED in the colors red, green, blue, white, amber and UV
- Functions: static colors, RGBAW+UV color mixture, automatic color change, built-in programs, dimmer, strobe effect, Master/Slave operation
- Dimmer speed (step response) adjustable
- Adjustable white balance
- 1, 3, 2 x 4, 5, 6, 8, 9, 18 or 22 DMX channels selectable
- Extremely compact housing in a beautiful design
- Ideal as floor spot
- Mounting bracket for installations on a stand or a crossbeam
- Locking possibility at the mounting bracket
- DMX-controlled operation or stand-alone operation
- Sound-control via built-in microphone; adjustable sensitivity via Control Board
- DMX512 control via any commercial DMX-controller
- Barndoors included in the delivery
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- 18 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; RDM
- Preprogrammed in Light J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 22°

Logistic

EAN / GTIN: 4026397531107 Weight: 8,60 kg Length: 0.43 m Width: 0.20 m Heigth: 0.31 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
Lamp type:	LED lamp
LED type:	18 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	1; 3; 5; 6; 8; 9; 18; 22; 4
Cooling:	Cooling fan
Control:	Stand-alone; DMX; RDM
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	40°
Housing color:	Black
Dimensions:	Width: 39,5 cm
	Depth: 16,5 cm Height: 24,5 cm
Weight:	8,10 kg
DMX channels:	1/3/2x4/5/6/8/9/18/22
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
LED type:	12 W HCL
LED number:	18
Beam angle:	22°
Dimensions (L x W x H):	395 x 165 x 245 mm
Legal specifications	
Special product:	Not designed for household room illumination
<u> </u>	Show effect lighting