

EUROLITE LED CLS-18 QCL RGBW 18x8W 12°

Compact spotlight with 18 x 8 W 4in1 QCL RGBW LED and DMX control

Art. No.: 51913889

GTIN: 4026397429688



The article is no longer in our assortment.

Features:

- Compact design
- 18 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color selection manual; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone; DMX
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 12°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397429688

Weight: 5,90 kg

Length: 0.39 m

Width: 0.26 m

Height: 0.21 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 114 W

IP classification: IP20

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	18 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 12; 15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; DMX
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	12°
Beam angle (1/2 peak):	12°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 34 cm Depth: 17 cm Height: 22 cm
Weight:	5,46 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting