eurolite®

EUROLITE LED Bow Bar 288/4 MCL

Fancy design, superlative performance!











The article is no longer in our assortment.

Features:

DMX channels:

- DMX512 control via regular DMX controller (occupies max. 27 channels)
- 4, 6, 9, 15, 24, 27 DMX channels selectable for various applications
- Controller connection and synchronisation via two 3-pin XLR plugs
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Further display settings possible: Display on or off, display upside-down
- Equipped with 288 x 5 mm LEDs (red: 96, green: 96, blue: 96) distributed in 4 segments, and 24 subsegments, respectively
- Operable in Stand-Alone Mode or DMX interface
- DMX-512 control possible via any commercial DMX-controller
- Sound-control via built-in microphone
- Functions: static colors; RGB color change, color mix settings, 10 built-in programs and strobe effect with variable speed; Master/Slave
- 4 LED Bow Bars make an LED circle
- One pair of knurled-head screws included in delivery with each device
- Locking possibility at the mounting bracket
- Ready for connection via IEC power cable included in delivery

Technical specifications: Power supply: 230 V AC, 50 Hz Power consumption: 90,00 W

4

Logistic

EAN / GTIN: 4026397403060 Weight: 3,25 kg Length: 0.76 m Width: 0.24 m Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Dimensions:	Width: 71 cm Depth: 200 cm Height: 15 cm
Weight:	2,60 kg
DMX channels:	max. 27
DMX connection:	3-pin XLR
LED type:	5 mm
LED number:	288
Beam angle:	30°
Dimensions (L x W x H):	710 x 200 x 150 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting