

EUROLITE Stage Panel 16 QCL RGB/WW LED

LED light effect bar with RGB/WW color mixing

Art. No.: 51913892

GTIN: 4026397718256



List price: 474.81 €

incl. 19% VAT.

Features:

- 16 powerful LEDs 7 W SMD 4in1 QCL RGB/WW (homogenous color mix)
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; Sound to light via Microphone; Master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); IR remote control
- Flicker-free
- With a beam angle of 15°
- With Mounting bracket
- 4 digit 7-segment LED display
- 4 pixel groups for dynamic running light effects
- 4 barn doors to avoid blinding the audience and for protection during transport
- Preprogrammed in Light Captain; Colorchief; EASY SHOW 2; EASY SHOW 3; Light J
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; Installation; Stage; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x barn door, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397718256

Weight: 5,80 kg

Length: 0.56 m

Width: 0.16 m

Height: 0.24 m

Technical specifications:

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 65 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | P-Con (gray), mounting version |
| Fuse: | T 1 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 16 x 7 W SMD 4in1 QCL RGB/WW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4; 5; 6; 8; 9; 16; 24 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; Sound to light via Microphone; Master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); IR remote control |
| Preprogrammed in: | Light Captain; Colorchief; EASY SHOW 2; EASY SHOW 3; Light J |
| Projection: | Flicker-free |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| Beam angle (1/10 peak): | 32° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 52,5 cm Depth: 9,9 cm Height: 18,1 cm |
| Weight: | 5,35 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |