eurolite®

EUROLITE Zoom4Bar QCL Bar

LED zoom effect bar with RGBW color mixing, incl. IR remote control









List price: 748.51 €

incl. 19% VAT.

Features:

- 4 segments for dynamic running lights
- 16 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
4 segments controlled separately
- Zoom motor driven
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
- Flicker-free
- With a beam angle of 5° 80°
- With double bracket
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x remote control

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W

Logistic

EAN / GTIN: 4026397643619 Weight: 10,25 kg Length: 0.65 m Width: 0.20 m Heigth: 0.36 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	16 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	5; 7; 9; 20; 26
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	5° - 80°
Beam angle (1/2 peak):	5 - 75°
Beam angle (1/10 peak):	10 - 80°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 57,5 cm
	Depth: 19,5 cm
	Height: 23 cm
Weight:	8,95 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting