

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

Art. No.: 51913905

GTIN: 4026397712834



List price: 355.81 €

incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 3 buttons on the remote control for saving your own settings
- 18 powerful LEDs 7 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 11°
- With mounting bracket
- OLED display
- Very quiet working noise
- Preprogrammed in Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
- Direct color temperature selection for 3100 preset values
- Rubber feet
- For application areas such as: Wedding/gala/events; stage; theater; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- **knurled screw**
- M4 thread

Package contents

- 1 x device, 1 x power cord, 1 x frost filter, 1 x remote control, 4 x knurled screw, 1 x user manual

Logistic

EAN / GTIN: 4026397712834

Weight: 5,14 kg

Length: 0.42 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	104 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	1 x PowerCON (gray)
Fuse:	T 6,3 A fuse fix on board
Lamp type:	LED lamp
LED type:	18 x 7 W 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
Preprogrammed in:	Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11° Frost filter 15°
Beam angle (1/10 peak):	26° Frost filter 37°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Length: 39,6 cm Width: 14,3 cm Height: 21,3 cm
Weight:	4,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F

Cable length:	Approx. 1,2 m
Frost filter	
Diameter mounting holes:	4 x Ø4,5mm
Material:	Plastic, 2 mm
Dimensions:	Width: 28,3 cm Height: 11,6 cm
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Barndoor	
Material:	Metal, 0,8 mm
Dimensions:	Width: 46,5 cm Height: 28,5 cm
Knurled screw	
Thread:	M4 thread x 8 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting