# eurolite®

## EUROLITE LED PAR-64 RGBW+UV short sil MK1

Versatile LED PAR-64 spot with 3 W LEDs

Art. No.: 51914074 GTIN: 4026397448597



## The article is no longer in our assortment.

#### Features:

- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller (occupies 7 channels)
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via rotary control
- Functions: Static colors, RGBW color blend, UV effects, internal programs, adjustable microphone sensitivity, dimmer and strobe settings via DMX, Master/Slave
- Perfect for decorative and illumination purposes (i.e. in stairways, cinemas, theaters, corridors or hallways, showrooms, etc.)
- Equipped with 49 x 3 W LEDs: 9 x red, 10 x green, 10 x blue, 10 x white, 10 x UV
- Beam angle approximately 20°
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Ready for connection via power cord with safety-plug
- Silver or black housing available

### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	160,00 W
Dimensions:	Width: 28 cm
	Depth: 27 cm
	Height: 33 cm

#### Logistic

EAN / GTIN: 4026397448597 Weight: 2,50 kg Length: 0.23 m Width: 0.23 m Heigth: 0.04 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	2,15 kg
DMX channels:	7
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	3 W
LED number:	49
Beam angle:	20°
Dimensions (L x W x H):	280 x 270 x 330 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting
Intended use:	Show effect lighting