

EUROLITE LED IP T-Bar 8 QCL Bar

Weather-proof (IP65) bar with RGBW color mixing, incl. IR remote control

Art. No.: 51914098

GTIN: 4026397701197



List price: 284.41 €

incl. 19% VAT.

Features:

- 8 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - Direct color selection for 19 preset colors
 - The device is cooled by passive convection cooling
 - Control via DMX; master/slave function; stand-alone; IR remote control
 - Flicker-free
 - With a beam angle of 20°
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Suitable for outdoor use
 - Silent operation
 - Mains input and output for power linking up to 8 units
 - Preprogrammed in Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
 - For application areas such as: Installation; restaurants, bars and hotels; architecture
 - Application possibility: Suspended; wall mounting
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x mounting bracket, 2 x screw, 2 x washer

Logistic

EAN / GTIN: 4026397701197

Weight: 4,05 kg

Length: 0.57 m

Width: 0.14 m

Height: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	40 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED type:	8 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) IP
DMX output:	3-pin XLR (F) IP
Cooling:	Passive convection cooling
Control:	DMX; master/slave function; stand-alone; IR remote control
Preprogrammed in:	Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic hard
Dimensions:	Length: 58,40 cm Depth: 10,00 cm Height: 12,65 cm
Weight:	3,68 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 3 x Ø8mm
Material:	Plastic hard, 4 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting