

EUROLITE LED IP T-PIX 12 HCL Bar

Weather-proof (IP65) bar with RGBAW+UV color mixing and pixel control

Art. No.: 51914111

GTIN: 4026397670158



Features:

- DMX and power terminals intelligently designed for easy wiring
- 12 LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response
- Strobe effect
- Direct color selection for 45 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR 4x6; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; LED EASY OPERATOR DELUXE; Colorchief
- Flicker-free
- With a beam angle of 25°
- With mounting bracket; with omega bracket
- LCD display
- Suitable for outdoor use
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397670158

Weight: 9,15 kg

Length: 1.08 m

Width: 0.19 m

Height: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	6; 11; 24; 41; 77
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR 4x6; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; LED EASY OPERATOR DELUXE; Colorchief
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	25°
Beam angle (1/2 peak):	25°
Beam angle (1/10 peak):	50°
Housing color:	Black
Attachment system:	2x mounting bracket Omega bracket
Display type:	LCD display
Dimensions:	Length: 99 cm Depth: 16 cm Height: 14 cm
Weight:	8.30 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x XLR cable
2 x mounting bracket