## eurolite®

## **EUROLITE LED IP T-PIX 8 QCL Bar**

Weather-proof (IP65) bar with RGBW color mixing and segment control

Art. No.: 51914116 GTIN: 4026397674965

## The article is no longer in our assortment.

#### Features:

- DMX and power terminals intelligently designed for easy wiring
- 384 powerful LEDs 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)<BR>8 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response
- Strobe effect
- Direct color selection for 32 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 120°
- With mounting bracket; with omega bracket
- Suitable for outdoor use
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Silent operation

IP classification:

- Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable, 2 x omega bracket

# Technical specifications: Power supply: 100-240 V AC, 50/60 Hz Power consumption: 130 W

IP65

#### Logistic

EAN / GTIN: 4026397674965 Weight: 9,15 kg Length: 1.08 m Width: 0.19 m Heigth: 0.26 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	384 x 0,4 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 25 Hz
DMX channels:	4; 9; 16; 37
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x mounting bracket Omega bracket
Dimensions:	Length: 99,0 cm Depth: 16,0 cm Height: 14,0 cm
Weight:	8,20 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting