

EUROLITE LED IP T1000 TCL Bar

Weather-proof bar (IP44) with 9 x 3 W 3in1 LED (RGB), 52 cm

Art. No.: 51914123

GTIN: 4026397591644



The article is no longer in our assortment.

Features:

- Equipped with 9 high-power 3 W 3in1 LEDs in the colors red, green and blue
- 2 x 3, 4, 5, 6 or 9 DMX channels selectable
- For architectural lighting
- Suitable for external use (IP44)
- For permanent installation, mounting brackets included
- Stepless RGB color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety-plug
- DMX control via every standard DMX controller
- 9 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1
- Flicker-free
- With a beam angle of 15°

Logistic

EAN / GTIN: 4026397591644

Weight: 3,00 kg

Length: 0.55 m

Width: 0.14 m

Height: 0.11 m

- Suitable for outdoor use IP44

Package contents

- 1 x adapter cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP44
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	9 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	3; 3; 4; 5; 6; 9
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	27°
Housing color:	Black
Dimensions:	Length: 51,5 cm Depth: 11 cm Height: 7,2 cm
Weight:	2,75 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting