

EUROLITE LED IP CCR-1200 QCL Wall Light incl. Flight Case

PRO outdoor spotlight (IP65) in case with 120 x 8 W 4in1 LED (RGBW)

Art. No.: 51914134

GTIN: 4026397573152



The article is no longer in our assortment.

Features:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX control via any standard DMX controller
- 4, 7, or 11 DMX channels selectable
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- For architectural lighting
- Suitable for external use (IP65)
- For permanent installation
- Equipped with 120 x 4in1 QCL LED in the colors red, green, blue and white
- Stepless RGBW color blend
- Color macros
- Dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Internal programs
- Programmable color change speed
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection via power cord with 3-pin 16A CEE plug
- Flightcase included in delivery
- 120 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by cooling fan
- Control via stand-alone; DMX; W-DMX by wireless solution
- Preprogrammed in Light'J; LED PC-Control 512
- Flicker-free
- With a beam angle of 15°

Logistic

EAN / GTIN: 4026397573152

Weight: 55,00 kg

Length: 0.72 m

Width: 0.50 m

Height: 0.80 m

Bulky product

- Suitable for outdoor use IP65

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	460 W
IP classification:	IP65
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	120 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 7; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; W-DMX by wireless solution
Preprogrammed in:	Light'J; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	48°
Housing color:	Black
Dimensions:	Width: 65 cm Depth: 58 cm Height: 67 cm
Weight:	54,90 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting