

## EUROLITE LED IP PAR 14x10W HCL

Weather-proof (IP65) spotlight with 6in1 HCL RGBWA/UV color mixing and frost filters

Art. No.: 51914172

GTIN: 4026397670233



**List price: 462.91 €**

incl. 19% VAT.

### Features:

- 14 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
  - Frost filter
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - Direct color selection for 25 preset colors
  - The device is cooled by passive convection cooling
  - Control via DMX; stand-alone; IR remote control
  - Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
  - Flicker-free
  - With a beam angle of 15°
  - With double bracket
  - LCD display
  - Mains input and output for power linking up to 8 units
  - Suitable for outdoor use IP65
  - For application areas such as: Installation; stage; rental; architecture
  - Silent operation
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 3 x frost filter, 1 x XLR cable, 2 x knurled screw, 1 x user manual

### Logistic

EAN / GTIN: 4026397670233

Weight: 8,10 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

## Technical specifications:

|                          |  |
|--------------------------|--|
| Power supply:            | 100-240 V AC, 50/60 Hz   |
| Power consumption:       | 95 W   |
| IP classification:       | IP65   |
| Protection class:        | Protection class I   |
| Power connection:        | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided)   |
| Power output:            | 1 x IP T-Con (F) mounting version  |
| Lamp type:               | LED lamp   |
| LED type:                | 14 x 10 W high-power 6in1 HCL RGBWA/UV<br>(homogenous color mix)   |
| Flash rate:              | 0 - 20 Hz  |
| Equipment:               | Frost filter   |
| DMX channels:            | 3; 5; 6; 8; 12   |
| DMX input:               | 3-pin XLR (M) mounting version IP  |
| DMX output:              | 3-pin XLR (F) mounting version IP  |
| Cooling:                 | Passive convection cooling   |
| Control:                 | DMX; stand-alone; IR remote control  |
| Preprogrammed in:        | Light´J; LED PC-Control 512; LED EASY<br>OPERATOR 4x6; LED EASY OPERATOR<br>DELUXE; Light´J; Light Captain; EASY SHOW 1;<br>EASY SHOW 2; EASY SHOW 3 |
| Projection:              | Flicker-free   |
| Beam angle:              | 15°  |
| Beam angle (1/2 peak):   | 15°<br>27°<br>30°<br>60°   |
| Housing color:           | Black matte  |
| Attachment system:       | Double bracket   |
| Display type:            | LCD display  |
| Material:                | Aluminum casting   |
| Dimensions:              | Width: 31 cm<br>Depth: 22,5 cm<br>Height: 36,5 cm  |
| Weight:                  | 6,80 kg  |
| Noise classification:    | Class 0 (no noise at all)  |
| Photobiological safety:  | Risk Group 0   |
| Mounting bracket         |  |
| Diameter mounting holes: | 3 x Ø11mm  |
| Material:                | Metal, 3 mm  |
| Power cord               |  |
| Cable construction:      | 3 x 1,0 mm² H05RN-F  |
| Cable length:            | Approx. 1,2 m  |
| Remote control           |  |

|                      |   |
|----------------------|---|
| Battery:             | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Frost filter         |   |
| Material:            | Plastic, 2 mm   |
| Dimensions:          | Diameter: Ø 20,5 cm                                     |
| XLR cable            |   |
| Cable length:        | Approx. 1,5 m   |
| Legal specifications |   |
| Special product:     | Not designed for household room illumination            |
| Intended use:        | Show effect lighting                                    |