eurolite®

EUROLITE LED IP PAR 12x3W TCL
Weather-proof DMX spotlight (IP65) with 12 x 3 W 3in1 LED (RGB)

Art. No.: 51914175

The article is no longer in our assortment.

Features:

- Equipped with 12 x 3 W RGB LED (3in1)
- Beam angle approximately 25°
- Locking possibility at the mounting bracket
- Ideal as floor spot via additional bracket
- RGB color change
- 7 color presets and 4 built-in programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Dimmer and strobe settings via DMX
- Suitable for external use (IP65)
- Perfect for architectural lighting in public places and buildings
- Addressing via control panel with 4-digit LED display
- Control via control panel with display or any regular DMX controller
- Feed-through output allows to power another device
- After every 8 spot the fixtures must have a renewed connection with the power mains
- 12 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
- With a beam angle of 25°
- Suitable for outdoor use IP65
  Package contents
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x adapter cable, 1 x terminating plug (power), 1 x terminating plug (DMX)

Logistic

EAN / GTIN: 4026397434859
Weight: 4,30 kg
Length: 0.28 m
Width: 0.27 m
Heigth: 0.32 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	50 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	12 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Dimensions:	Width: 24 cm Depth: 20 cm Height: 32 cm
Weight:	3,85 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting