

EUROLITE LED IP PAR 14x8W QCL

Weather-proof (IP65) spotlight with RGBW color mixing, incl. diffuser discs

Art. No.: 51914178

GTIN: 4026397645217



List price: 391.51 €

incl. 19% VAT.

Features:

- Stepless color blend, color change, color fade, dimmer and strobe effect
- Mains input and output for power linking up to 8 units
- 14 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Direct color selection for 18 preset colors
- Can be operated in 2; 3; 4; 8 CH mode
- The device is cooled by passive convection
- Controlling by stand-alone; DMX; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Effect: Strobe effect
- With a beam angle of 15°
- With Mounting bracket
- With double bracket
- Monochrome LCD display for easy controlling
- Suitable for outdoor use

Logistic

EAN / GTIN: 4026397645217

Weight: 8,33 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

Package contents

- 1 x Device, 1 x User manual, 1 x Power cord, 1 x Remote control, 1 x Battery, 3 x Diffusor cover, 1 x XLR cable, 2 x Knurled screw

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 90 W

IP classification: IP65

Protection class:	Class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	14 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection
Control:	Stand-alone; DMX; Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; IR remote control
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Mounting bracket Double bracket
Display type:	Monochrome LCD display
Dimensions:	Width: 31 cm Depth: 22,5 cm Height: 36,5 cm
Weight:	7,15 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting