eurolite®

EUROLITE AKKU LED IP FL-20 COB RGB Spot

Weather-proof floodlight with battery, 20 W RGB LED and remote control

Art. No.: 51914201

GTIN: 4026397515510

The article is no longer in our assortment.

Features:

- RGB floodlight with one 20 W COB LED
- Ideal LED luminary for outdoor use
- Weather-proof housing (IP44)
- Operation via built-in rechargeable lithium-ion battery with up to 4 hours operating time
- Adjustabel inclination angle
- Diverse settings: solid colors, brightness, internal programs
- Infrared-remote control in credit card format included in delivery
- Charging via 12 V power unit or via automobile on-board voltage plug connector (both included in delivery)
- 1 powerful LED 20 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via on/off switch on device; IR remote control
- With a beam angle of 120°
- Suitable for outdoor use IP44

device

- Cordless, flexible and versatile
- Battery operation up to 4,5h depending on program used

Package contents

- 1 x device, 1 x remote control

Logistic

EAN / GTIN: 4026397515510

Weight: 1,72 kg

Length: 0.20 m

Width: 0.23 m

Heigth: 0.16 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
	Or

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	12/24V DC
Power consumption:	16,00 W
IP classification:	IP44
Power connection:	Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Mains input via Coaxial power connector (M) mounting version power supply cord with cigarette lighter plug (provided)
Lamp type:	LED lamp
LED:	1 x 20 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling
Control:	On/off switch on device; IR remote control
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Dimensions:	Width: 21,5 cm Depth: 18,5 cm Height: 25,5 cm
Weight:	1,60 kg
Device	
Battery pack type:	1 x lithium ion 7,4 V, 4400 mAh, 33 Wh
Battery pack:	Battery operation up to 4,5h depending on program used Recharging time 4,5h
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.