

EUROLITE AKKU LED IP FL-5 COB 3200K

Weather-proof floodlight with rechargeable battery and 5 W LED

Art. No.: 51914203 GTIN: 4026397592221











Features:

- Floodlight with one white 5W COB LED
- Ideal LED luminary for outdoor use
- Operation via built-in rechargeable lithium-ion battery with up to 6 hours operating time
- Including portable stand with comfortable handle
- The inclination angle can be adjusted via the fixation screws
- Designed for standing or hanging operation
- Rechargeable battery pack
- Charging via 5 V charger or via automobile on-board voltage plug (both included in delivery)
- 1 powerful LED COB (chip-on-board) warm white (WW)
- The device is cooled by passive convection cooling
- Control via on/off switch on device
- With a beam angle of 120°
- Suitable for outdoor use IP44
- Silent operation

device

- Cordless, flexible and versatile
- Battery operation up to 6h depending on program used

Package contents

- 1 x device

Technical specifications:

Power supply:

100-240 V AC, 50/60 Hz 5V DC 500 mA

Logistic

EAN / GTIN: 4026397592221

Weight: 1,00 kg Length: 0.20 m Width: 0.20 m Heigth: 0.15 m

	12/24 00
	5V DC 1000 mA
Power consumption:	5 W
IP classification:	IP44
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with cigarette lighter plug (provided)
	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
	Battery/battery pack
Lamp type:	LED lamp
LED type:	1 x COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	On/off switch on device
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Dimensions:	Width: 14,4 cm
	Depth: 18,5 cm
	Height: 26,5 cm
Weight:	0,86 kg
Noise classification:	Class 0 (no noise at all)
Device	
Battery pack type:	1 x lithium ion 3,7 V, 2200 mAh, 8 Wh
Battery pack:	Battery operation up to 6h depending on program used
	Recharging time 5h

Or 12/24V DC