

## EUROLITE LED IP Triple Eye Hybrid

Weatherproof (IP65) 3-fold blinder with RGB/WW color mixing and white effect LEDs

Art. No.: 51914211

GTIN: 4026397753851



**List price: 831.81 €**

incl. 19% VAT.

### Description:

This weatherproof blinder features three powerful LED eyes based on red, green, blue, and warm white color mixing. It is suitable for both colored and white light applications, with each eye individually controllable for added creative flexibility.

The system is complemented by two cold white LED strips positioned above and below the eyes. These can also be controlled individually and used to create dynamic animations.

### Features:

- 3 LEDs 100 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) LEDs controlled separately
- 108 LEDs 0.5 W SMD 5050 cold white (CW) 18 segments controlled separately
- Dimmer electronic; color change; color fade; color selection adjustable
- Blinder effect; wash effect; strobe effect
- 6 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function
- Flicker-free
- DMX fail mode (blackout; hold; full on; static; auto)
- With a beam angle of 22°
- Variable color temperature 1800 K - 8000 K
- With mounting bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector

### Logistic

EAN / GTIN: 4026397753851

Weight: 8,85 kg

Length: 0.46 m

Width: 0.28 m

Height: 0.25 m

- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; theater; rental
- Application possibility: Suspended; on stand
- Fixtures available for Light Captain

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm <sup>2</sup> H05RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	3 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) 108 x 0.5 W SMD 5050 cold white (CW)
Flash rate:	0.5 - 18 Hz
DMX channels:	5; 10; 12; 18-1; 18-2; 36
DMX input:	3-pin XLR (F) mounting version IP
DMX output:	3-pin XLR (M) mounting version IP
Cooling:	4 x cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	7800 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	40°
Color temperature:	1800K - 8000K adjustable
Lamp life:	20000 h
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
Diameter mounting holes:	3 x Ø11mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 40.40 cm Depth: 19.95 cm Height: 24.00 cm
Weight:	8.30 kg
Noise classification:	Class 2 (slight noise)

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### **Scope of delivery:**

---

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery