

## EUROLITE LED IP PAR 12x8W QCL Spot

Weather-proof (IP65) spotlight with 12 x 4in1 LED and RGBW color mixing

Art. No.: 51914231

GTIN: 4026397672114



**List price: 379.61 €**

incl. 19% VAT.

### Features:

- 12 high-power 8 W RGBW LEDs (4in1)
- Suitable for external use (IP65)
- Auto, master/slave and DMX mode
- Built-in auto show programs
- Direct color selection for 25 preset colors
- Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
- Addressing via control panel with LCD and four operating buttons
- Convenient wireless control via included IR remote control EUROLITE IR-7
- 2 diffuser covers (40° und 15x60°) optionally available, not included in delivery
- Swivel mounting bracket
- Additional bracket for floor use
- IP T-Con terminals for power linking up to 8 units
- LED: 12 x 8 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 3; 4; 5; 6; 10 CH mode
- The device is cooled by passive convection
- Controlling by DMX; IR remote control; Stand-alone
- Is in Light J Software; EUROLITE LED PC-Control 512 software; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE already preprogrammed
- Flicker-free projection
- Suitable for outdoor use

### Logistic

EAN / GTIN: 4026397672114

Weight: 5,75 kg

Length: 0.35 m

Width: 0.32 m

Height: 0.20 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Class I
Power connection:	Mains input IP T-Con (M) mounting version Power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	12 x 8 W 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection
Control:	DMX; IR remote control; Stand-alone; Light J Software; EUROLITE LED PC-Control 512 software; EASY SHOW; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	29°
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 28,5 cm Depth: 15,3 cm Height: 31,35 cm
Weight:	5,20 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting