# eurolite®

### EUROLITE LED IP PAR 3x9W SCL Spot

Weather-proof (IP65) spotlight with 3 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

Art. No.: 51914235 GTIN: 4026397683981









## List price: 236.81 €

incl. 19% VAT.

#### Features:

- 3 powerful LEDs 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Preprogrammed in Light J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; stage; rental; architecture
- Application possibility: On stand; suspended
- Package contents
- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

#### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W
IP classification:	IP65
Protection class:	Protection class I

#### Logistic

EAN / GTIN: 4026397683981 Weight: 3,20 kg Length: 0.19 m Width: 0.19 m Heigth: 0.29 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power output:   IP T-Con (F) mounting version     LED type:   3 x 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)     Flash rate:   0 - 20 Hz     DMX channels:   3; 5; 7; 9; 13     DMX input:   3-pin XLR (M) mounting version IP     DMX output:   3-pin XLR (F) mounting version IP     Cooling:   Passive convection cooling     Cooling:   Passive convection cooling     Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm Depth: 17,1 cm Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese builit-in     Legal specific	Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
(homogenous color mix)     Flash rate:   0 - 20 Hz     DMX channels:   3; 5; 7; 9; 13     DMX input:   3-pin XLR (M) mounting version IP     DMX output:   3-pin XLR (F) mounting version IP     Cooling:   Passive convection cooling     Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Power output:	IP T-Con (F) mounting version
DMX channels:   3; 5; 7; 9; 13     DMX input:   3-pin XLR (M) mounting version IP     DMX output:   3-pin XLR (F) mounting version IP     Cooling:   Passive convection cooling     Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/12 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm Depth: 17,1 cm Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	LED type:	
DMX input:   3-pin XLR (M) mounting version IP     DMX output:   3-pin XLR (F) mounting version IP     Cooling:   Passive convection cooling     Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm Depth: 17,1 cm Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Legal specifications   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Not designed for household room illumination	Flash rate:	0 - 20 Hz
DMX output:   3-pin XLR (F) mounting version IP     Cooling:   Passive convection cooling     Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light 'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:     Not designed for household room illumination   Special product:	DMX channels:	3; 5; 7; 9; 13
Cooling:   Passive convection cooling     Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	DMX input:	3-pin XLR (M) mounting version IP
Control:   Stand-alone; IR remote control; DMX     Preprogrammed in:   Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     Legal specifications   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	DMX output:	3-pin XLR (F) mounting version IP
Preprogrammed in:   Light 'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Eattery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Cooling:	Passive convection cooling
SHOW 2; EASY SHOW 3     Projection:   Flicker-free     Beam angle:   15°     Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Eattery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Control:	Stand-alone; IR remote control; DMX
Beam angle:   15°     Beam angle (1/10 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:     Not designed for household room illumination	Preprogrammed in:	
Beam angle (1/2 peak):   15°     Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Projection:	Flicker-free
Beam angle (1/10 peak):   30°     Housing color:   Black     Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm Depth: 17,1 cm Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Beam angle:	15°
Housing color: Black   Attachment system: Double bracket   Display type: LCD display   Dimensions: Width: 21,5 cm   Depth: 17,1 cm Height: 24,4 cm   Weight: 3,00 kg   Noise classification: Class 0 (no noise at all)   Photobiological safety: Risk Group 0   Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in   Legal specifications Special product:	Beam angle (1/2 peak):	15°
Attachment system:   Double bracket     Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Beam angle (1/10 peak):	30°
Display type:   LCD display     Dimensions:   Width: 21,5 cm     Depth: 17,1 cm   Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Housing color:	Black
Dimensions: Width: 21,5 cm   Depth: 17,1 cm Height: 24,4 cm   Weight: 3,00 kg   Noise classification: Class 0 (no noise at all)   Photobiological safety: Risk Group 0   Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in   Legal specifications Special product:	Attachment system:	Double bracket
Depth: 17,1 cm     Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Display type:	LCD display
Height: 24,4 cm     Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Image: Second Stress St	Dimensions:	Width: 21,5 cm
Weight:   3,00 kg     Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications     Special product:   Not designed for household room illumination		•
Noise classification:   Class 0 (no noise at all)     Photobiological safety:   Risk Group 0     Remote control   1     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:		Height: 24,4 cm
Photobiological safety:   Risk Group 0     Remote control   Image: Second Se	Weight:	3,00 kg
Remote control     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications     Special product:   Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:     Not designed for household room illumination	Photobiological safety:	Risk Group 0
built-in   Legal specifications   Special product: Not designed for household room illumination	Remote control	
Special product: Not designed for household room illumination	Battery:	
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting