

EUROLITE LED IP Tourlight 120 WW

Weather-proof LED spotlight (IP65) with warm white 100 W LED, CRI >95

Art. No.: 51914251

GTIN: 4026397661927

The article is no longer in our assortment.

Features:

- Ideal for architectural and front lighting at open air events
 - 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
 - The device is cooled by temperature-controlled fan
 - Control via DMX; master/slave function
 - Flicker-free
 - With a beam angle of 12°
 - Very high color rendering index (CRI)
 - With omega bracket; with double bracket
 - Suitable for outdoor use IP65
 - Exact 16 bit resolution at Dimmer
 - Dimmer curves with adjustable response; Dimmer speed (step response) adjustable
 - Strobe effect
 - Preprogrammed in LED PC-Control 512; Light Captain
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Installation; stage; theater; architecture
 - Silent operation
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x cover

Logistic

EAN / GTIN: 4026397661927

Weight: 6,60 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.45 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 110 W

IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	1 - 20 Hz
DMX channels:	1; 3
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	DMX; master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	26°
Color temperature:	3200K
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Omega bracket Double bracket
Dimensions:	Width: 27 cm Depth: 27 cm Height: 30,5 cm
Weight:	5,90 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting