

## EUROLITE LED IP TL-3 QCL Trusslight

Weather-proof LED spot (IP65) ideal as trusslight or uplight with bright 3x10W RGBW LED

Art. No.: 51914270

GTIN: 4026397727333



List price: 296.31 €

incl. 19% VAT.

### Features:

- Compact and bright
- 3 powerful LEDs 10 W 4in1 QCL RGBW (homogenous color mix)
- Additional frost filter provides a wide, soft and homogeneous light
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Uplight effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Control via stand-alone; DMX; Master/slave function; IR remote control; RDM
- 3 buttons on the remote control for saving your own settings
- With a beam angle of 10°
- Flicker-free
- OLED display
- Mains input and output for power linking up to 8 units
- The device is cooled by passive convection cooling
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; video and photography
- Silent operation
- Application possibility: Standing; suspended
- Threaded inserts for suspended installation
- Preprogrammed in EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light J
- Built with SEETRONIC connector

### Package contents

### Logistic

EAN / GTIN: 4026397727333

Weight: 2,12 kg

Length: 0.20 m

Width: 0.18 m

Height: 0.20 m

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x diffusor cover, 1 x remote control, 1 x battery, 3 x knurled screw

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	3 x 10 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Master/slave function; IR remote control; RDM
Preprogrammed in:	EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 20°
Beam angle (1/10 peak):	20° Frost filter 45°
Housing color:	Black
Attachment system:	2x M10 thread
Display type:	OLED display
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 13,1 cm Depth: 11,8 cm Height: 15,3 cm
Weight:	1,90 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting