eurolite®

EUROLITE LED FLS-6 white 7500K 40° IP54

Brilliant LED floodlight stands by you!

Art. No.: 51914405 GTIN: 4026397272659











The article is no longer in our assortment.

Features:

- Floodlight with high power LEDs
- Ideal LED luminary for outdoor use
- Indoors or outdoors, usable everywhere
- Including portable stand with comfortable handle and protective grille
- The inclination angle can be adjusted via the fixation screw
- Designed for standing operation only
- Extremely compact housing and an appealing design
- Ready for connection with 2.8 m power cord and safety-plug
- Available in 4 colors and 2 color temperatures (white)
- Available in 10° or in 40° versions of the beam reflection angle
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP54
Dimensions:	Width: 16 cm
	Depth: 17,5 cm
	Height: 23 cm
Power consumption:	6 W
LED number:	6 x 1 W

Logistic

EAN / GTIN: 4026397272659 Weight: 1,45 kg Length: 0.17 m Width: 0.14 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Beam angle:	40°
Protection grade:	IP54
Dimensions:	160 x 175 x 230 mm
Weight:	1.2 kg