eurolite®

EUROLITE LED IP FL-8 3000K 60°

Outdoor floodlight (IP56) with 8 x 1 W LED and 60° beam angle

Art. No.: 51914525 GTIN: 4026397421804









The article is no longer in our assortment.

Features:

- Add highlights to your house and garden
- Compact design
- Alternative articles with colored LEDs and a beam reflection angle of 30° or 60° also available
- 8 powerful LEDs 1 W high-power warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 60°
- With mounting bracket
- Suitable for outdoor use IP56
- Various versions available
- Silent operation
- For application areas such as: Restaurants, bars and hotels; small rental; architecture; installation
- Application possibility: Suspended Package contents
- 1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	13 W
IP classification:	IP56
Protection class:	Protection class I

Logistic

EAN / GTIN: 4026397421804 Weight: 1,00 kg Length: 0.07 m Width: 0.18 m Heigth: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,9 m
Lamp type:	LED lamp
LED type:	8 x 1 W high-power warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	60°
Beam angle (1/2 peak):	60°
Color temperature:	3000K
Luminous flux:	500 lm
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 17 cm Depth: 5 cm Height: 15 cm
Weight:	0,93 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm