eurolite®

EUROLITE LED IP FL-50 COB 3000K 120°

Brilliant floodlight with LED technology

Art. No.: 51914585 GTIN: 4026397446364



The article is no longer in our assortment.

Features:

- Add highlights to your house and garden
- Ideal LED luminary for indoor or outdoor use
- The weather-resistant housing also allows operation during bad weather
- For permanent installation, mounting bracket included
- Extremely compact housing in an appealing design
- Particularly bright illuminating power
- 2 color temperatures of the white LEDs available: 6400 K or 3000 K
- Beam reflection angle of 120°
- Ready for connection via power cord with safety-plug
- 1 powerful LED 50 W COB (chip-on-board) warm white (WW)
- The device is cooled by passive convection cooling
- With a beam angle of 120°
- Suitable for outdoor use IP54

Technical specifications:

100-240 V AC, 50/60 Hz
50 W
IP54
Fixed power supply cord with safety plug
LED lamp
1 x 50 W COB (chip-on-board) warm white (WW)

Logistic

EAN / GTIN: 4026397446364 Weight: 2,65 kg Length: 0.29 m Width: 0.25 m Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cooling:	Passive convection cooling
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Silver
Color:	Clear
Dimensions:	Width: 28,5 cm Depth: 23,5 cm Height: 14,5 cm
Weight:	2,45 kg
Protection grade:	IP54
LED type:	Array 50 W
LED number:	1
Beam angle:	120°
Color temperature:	3000 K
Light ouput intensity:	3350 Lm
Dimensions (L x W x H):	285 x 235 x 145 mm