# eurolite®

## EUROLITE LED IP FL-10 SMD RGB

Outdoor floodlight (IP65) with RGB LEDs and IR remote control

Art. No.: 51914602

GTIN: 4026397680607







### List price: 35.58 €

incl. 19% VAT.

#### Features:

- Extremely slim housing in an appealing design
- 36 powerful LEDs SMD 2835 R/G/B
- Color change automatic; program selection manual; color selection manual; color fade adjustable; program speed adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 16 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control
- With a beam angle of 82°
- With mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; party room; small rental
- Application possibility: Suspended Package contents
- 1 x spotlight, 1 x remote control, 1 x user manual

#### **Technical specifications:**

Power consumption:	10 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

#### Logistic

EAN / GTIN: 4026397680607 Weight: 0,53 kg Length: 0.18 m Width: 0.15 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable construction:	3 x 1,0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	36 x SMD 2835 R/G/B
Cooling:	Passive convection cooling
Control:	IR remote control
Beam angle:	82°
Beam angle (1/2 peak):	82°
Color of light:	Switching colors
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 13,5 cm
	Depth: 3 cm
	Height: 12,3 cm
Weight:	0,46 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø6mm
Material:	Metal, 1,5 mm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in