#### Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## eurolite®

### EUROLITE LED IP FL-50 COB RGB 120° RC

Outdoor floodlight (IP65) with 50 W COB LED (RGB) and IR remote control

Art. No.: 51914610 GTIN: 4026397455458

# List price: 106.98 €

incl. 19% VAT.

### Features:

- Add highlights to your house and garden
- Compact design
- 1 powerful LED 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Direct color selection for 16 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control
- With a beam angle of 120°
- With mounting bracket
- Suitable for outdoor use IP65
- Dimmer electronic; color change adjustable; color fade adjustable
- Strobe effect
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; party room; small rental
- Application possibility: Suspended
- Package contents1 x spotlight, 1 x remote control, 1 x user manual

### **Technical specifications:**

| Power supply:      | 230 V AC, 50 Hz    |
|--------------------|--------------------|
| Power consumption: | 50 W               |
| IP classification: | IP65               |
| Protection class:  | Protection class I |

### Logistic

EAN / GTIN: 4026397455458 Weight: 2,15 kg Length: 0.29 m Width: 0.25 m Heigth: 0.17 m











| Power connection:        | Fixed power supply cord with safety plug                         |
|--------------------------|--|
| Cable construction:      | 3 x 1,0 mm <sup>2</sup> H05RN-F                                  |
| Cable length:            | Approx. 1,6 m  |
| Lamp type:               | LED lamp   |
| LED type:                | 1 x 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix) |
| Cooling:                 | Passive convection cooling                                       |
| Control:                 | Stand-alone; IR remote control                                   |
| Beam angle:              | 120°   |
| Beam angle (1/2 peak):   | 120°   |
| Color of light:          | Switching colors   |
| Housing color:           | Silvergrey   |
| Attachment system:       | Mounting bracket   |
| Material:                | Aluminum casting   |
| Dimensions:              | Width: 28,5 cm<br>Depth: 14,5 cm<br>Height: 23,5 cm              |
| Weight:                  | 2,00 kg  |
| Noise classification:    | Class 0 (no noise at all)  |
| Remote control           |  |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in          |
| Mounting bracket         |  |
| Diameter mounting holes: | 3 x Ø10mm  |
| Material:                | Metal, 1,5 mm  |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination                     |
| Intended use:            | Show effect lighting   |
|                          |  |