

EUROLITE LED IP FL-80 COB 6000K 120° SLIM

LED outdoor floodlight (IP65) with extremely flat housing and 80 W LED

Art. No.: 51914740 GTIN: 4026397547474







The article is no longer in our assortment.

Features:

- Add highlights to your house and garden
- Equipped with 1 x 80 W COB LED
- Extremely flat housing
- Ideal LED luminary for outdoor use
- The weather-resistant housing (IP65) also allows operation during bad weather
- For permanent installation, mounting bracket included
- Extremely compact housing in an appealing design
- Particularly bright illuminating power of the LEDs
- Beam reflection angle of 120°
- Ready for connection via power cord with safety-plug
- 1 powerful LED 80 W COB (chip-on-board) cold white (CW)
- The device is cooled by passive convection cooling
- With a beam angle of 120°
- Suitable for outdoor use IP65

Technical specifications:

| Power supply: | 230 V AC, 50 Hz |
|--------------------|--|
| Power consumption: | 80 W |
| IP classification: | IP65 |
| Power connection: | Fixed power supply cord with safety plug |
| Lamp type: | LED lamp |

Logistic

EAN / GTIN: 4026397547474

Weight: 2,60 kg Length: 0.36 m Width: 0.33 m Heigth: 0.10 m

| LED: | 1 x 80 W COB (chip-on-board) cold white (CW) |
|-------------------------|--|
| Cooling: | Passive convection cooling |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Housing color: | Grey |
| Dimensions: | Width: 41,6 cm |
| | Depth: 32 cm |
| | Height: 24,6 cm |
| Weight: | 2,15 kg |
| Protection grade: | IP65 |
| LED type: | 80 W COB LED |
| LED number: | 1 |
| Beam angle: | 120° |
| Color temperature: | 6000 K |
| Dimensions (L x W x H): | 41.5 x 320 x 246 mm |