# eurolite®

## EUROLITE LED IP FL-80 COB 6000K 120° SLIM

LED outdoor floodlight (IP65) with extremely flat housing and 80 W LED

Art. No.: 51914740 GTIN: 4026397547474

A.S.



## The article is no longer in our assortment.

### Features:

- Add highlights to your house and garden
- Equipped with 1 x 80 W COB LED
- Extremely flat housing
- Ideal LED luminary for outdoor use
- The weather-resistant housing (IP65) also allows operation during bad weather
- For permanent installation, mounting bracket included
- Extremely compact housing in an appealing design
- Particularly bright illuminating power of the LEDs
- Beam reflection angle of 120°
- Ready for connection via power cord with safety-plug
- 1 powerful LED 80 W COB (chip-on-board) cold white (CW)
- The device is cooled by passive convection cooling
- With a beam angle of 120°
- Suitable for outdoor use IP65

### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	80 W
IP classification:	IP65
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp

#### Logistic

EAN / GTIN: 4026397547474 Weight: 2,60 kg Length: 0.36 m Width: 0.33 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

LED:	1 x 80 W COB (chip-on-board) cold white (CW)
Cooling:	Passive convection cooling
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Grey
Dimensions:	Width: 41,6 cm
	Depth: 32 cm
	Height: 24,6 cm
Weight:	2,15 kg
Protection grade:	IP65
LED type:	80 W COB LED
LED number:	1
Beam angle:	120°
Color temperature:	6000 K
Dimensions (L x W x H):	41.5 x 320 x 246 mm