eurolite®

EUROLITE LED IP FL-100 6400K

Flat IP54 outdoor floodlight with 140 SMD-LEDs cold white (CW)

Art. No.: 51914780 GTIN: 4026397626117











List price: 165.41 €

incl. 19% VAT.

Features:

- Add highlights to your house and garden
- Extremely flat housing
- 140 powerful LEDs SMD 3030 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 70°
- With mounting bracket
- Suitable for outdoor use IP54
- For application areas such as: Installation; architecture
- Silent operation
- Application possibility: Suspended
- Package contents1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	100 W
IP classification:	IP54
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,9 m

Logistic

EAN / GTIN: 4026397626117 Weight: 4,50 kg Length: 0.39 m Width: 0.31 m Heigth: 0.16 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp
LED type:	140 x SMD 3030 cold white (CW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	70°
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	110
Color of light:	Cold white CW >5000 K
Color temperature:	6400K
Housing color:	Silver
Attachment system:	Mounting bracket
Dimensions:	Width: 28,5 cm
	Depth: 9 cm
	Height: 38,2 cm
Weight:	4,14 kg
Noise classification:	Class 0 (no noise at all)