EUROLITE LED IP FL-30 SMD green

Flat IP65 outdoor floodlight with 60 SMD-LEDs green (G)

Art. No.: 51914952

GTIN: 4026397676761

List price: 47.48 €

incl. 19% VAT.

Features:

- 60 powerful LEDs 0,5 W SMD 5730 green (G)
- The device is cooled by passive convection cooling
- Control via plug and play
- With Mounting bracket
- Suitable for outdoor use IP65
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

  Package contents
- 1 x spotlight, 1 x user manual

Logistic

EAN / GTIN: 4026397676761

Weight: 1,10 kg

Length: 0.25 m

Width: 0.20 m

Heigth: 0.07 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp
LED type:	60 x 0,5 W SMD 5730 green (G)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	80°
Beam angle (1/10 peak):	120°
Color of light:	Green
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 22 cm Depth: 3,5 cm Height: 17,8 cm
Weight:	1,01 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.