eurolite®

EUROLITE LED IP FL-20 SMD CW

Flat outdoor floodlight (IP66) with white SMD LEDs









List price: 17.73 €

incl. 19% VAT.

Features:

- 30 powerful LEDs SMD 2835 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

- 1 x device, 1 x user manual

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	22 W
IP classification:	IP66
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1 m

Logistic

EAN / GTIN: 4026397695816 Weight: 0,40 kg Length: 0.16 m Width: 0.07 m Heigth: 0.12 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp
LED type:	30 x SMD 2835 cold white (CW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color temperature:	6000K
Luminous flux:	1756 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 13 cm
	Depth: 2,3 cm
	Height: 10 cm
Weight:	0,36 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	963751
Mounting bracket	
Diameter mounting holes:	1 x Ø8mm; 2 x Ø6mm
Material:	Metal, 1,5 mm