

## EUROLITE LED IP FL-50 SMD WW

Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915030

GTIN: 4026397695908



**List price: 35.58 €**

incl. 19% VAT.

### Features:

- 64 powerful LEDs SMD 2835 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With Mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

#### Package contents

- 1 x device, 1 x user manual

### Logistic

EAN / GTIN: 4026397695908

Weight: 0,70 kg

Length: 0.21 m

Width: 0.07 m

Height: 0.17 m

### Technical specifications:

|                     |  |
|---------------------|--|
| Power supply:       | 230 V AC, 50 Hz                          |
| Power consumption:  | 50 W                                     |
| IP classification:  | IP66                                     |
| Protection class:   | Protection class I                       |
| Power connection:   | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 1,0 mm <sup>2</sup> H05RN-F          |
| Cable length:       | Approx. 1 m                              |

|                                  |  |
|----------------------------------|--|
| Lamp type:                       | LED lamp   |
| LED:                             | 64 x SMD 2835 warm white (WW)                    |
| Color temperature:               | 3000K  |
| Cooling:                         | Passive convection cooling                       |
| Control:                         | Plug and play                                    |
| Beam angle (1/2 peak):           | 70°  |
| Beam angle (1/10 peak):          | 120°   |
| Color rendering index (CRI):     | 80 Ra  |
| Luminous flux:                   | 4320 lm  |
| Housing color:                   | Black matte                                      |
| Attachment system:               | Mounting bracket                                 |
| Material:                        | Aluminum casting                                 |
| Dimensions:                      | Width: 25 cm<br>Depth: 2,6 cm<br>Height: 19,2 cm |
| Weight:                          | 630 g  |
| Noise classification:            | Class 0 (no noise at all)                        |
| Energy efficiency class (A - G): | F  |
| Mounting bracket                 |  |
| Diameter mounting holes:         | 1 x Ø8mm; 2 x Ø6mm                               |
| Material:                        | Metal, 1,5 mm                                    |