# eurolite®

### EUROLITE LED IP FL-150 SMD WW

Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915050 GTIN: 4026397695960









## List price: 105.91 €

incl. 19% VAT.

#### Features:

- 180 powerful LEDs SMD 2835 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- With pressure compensation membrane
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended Package contents
- 1 x device, 1 x user manual

#### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	155 W
IP classification:	IP66
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F

#### Logistic

EAN / GTIN: 4026397695960 Weight: 1,90 kg Length: 0.34 m Width: 0.06 m Heigth: 0.26 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	180 x SMD 2835 warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color temperature:	3000K
Color rendering index (CRI):	82 Ra
Luminous flux:	13453 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 33 cm
	Depth: 3,7 cm
	Height: 27,3 cm
Weight:	1,80 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	966921
Mounting bracket	
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm