

EUROLITE LED IP FL-300 SMD CW

Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915075

GTIN: 4026397695861









List price: 177.31 €

incl. 19% VAT.

Features:

- 396 powerful LEDs SMD 2835 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- With pressure compensation membrane
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

1 x device, 1 x user manual

Logistic

EAN / GTIN: 4026397695861

Weight: 4,30 kg Length: 0.45 m Width: 0.37 m Heigth: 0.07 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	310 W
IP classification:	IP66
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F

LED type: LED type: 396 x SMD 2835 cold white (CW) Cooling: Passive convection cooling Control: Plug and play Beam angle (1/2 peak): 70° Beam angle (1/10 peak): 120° Color temperature: 6000K Color rendering index (CRI): 80 Ra Luminous flux: 28049 Im Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm Material: Metal, 3 mm	Cable length:	Approx. 1 m
Cooling: Passive convection cooling Control: Plug and play Beam angle (1/2 peak): 70° Beam angle (1/10 peak): 120° Color temperature: 6000K Color rendering index (CRI): 80 Ra Luminous flux: 28049 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm	Lamp type:	LED lamp
Control: Plug and play Beam angle (1/2 peak): 70° Beam angle (1/10 peak): 120° Color temperature: 6000K Color rendering index (CRI): 80 Ra Luminous flux: 28049 Im Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm	LED type:	396 x SMD 2835 cold white (CW)
Beam angle (1/2 peak): To° Beam angle (1/10 peak): Color temperature: 6000K Color rendering index (CRI): 80 Ra Luminous flux: 28049 Im Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm	Cooling:	Passive convection cooling
Beam angle (1/10 peak): Color temperature: 6000K Color rendering index (CRI): 80 Ra Luminous flux: 28049 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Control:	Plug and play
Color temperature: Color rendering index (CRI): 80 Ra Luminous flux: 28049 lm Housing color: Black matte Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Beam angle (1/2 peak):	70°
Color rendering index (CRI): Luminous flux: 28049 lm Housing color: Black matte Attachment system: Mounting bracket Material: Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Beam angle (1/10 peak):	120°
Luminous flux: Housing color: Black matte Attachment system: Material: Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: Vidential: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Color temperature:	6000K
Housing color: Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Color rendering index (CRI):	80 Ra
Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm	Luminous flux:	28049 lm
Material: Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Housing color:	Black matte
Dimensions: Width: 44,5 cm Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm	Attachment system:	Mounting bracket
Depth: 4,7 cm Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm	Material:	Aluminum casting
Height: 37,5 cm Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm	Dimensions:	Width: 44,5 cm
Weight: 4,00 kg Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm		Depth: 4,7 cm
Noise classification: Class 0 (no noise at all) Energy efficiency class (A - G): Mounting bracket Diameter mounting holes: 3 x Ø10mm		Height: 37,5 cm
Energy efficiency class (A - G): F Mounting bracket Diameter mounting holes: 3 x Ø10mm	Weight:	4,00 kg
Mounting bracket Diameter mounting holes: 3 x Ø10mm	Noise classification:	Class 0 (no noise at all)
Diameter mounting holes: 3 x Ø10mm	Energy efficiency class (A - G):	F
	Mounting bracket	
Material: Metal, 3 mm	Diameter mounting holes:	3 x Ø10mm
	Material:	Metal, 3 mm