# eurolite®

## EUROLITE LED SLS-9 Hybrid HCL

Flat spotlight with strobe and UV effects, incl. IR remote control













## The article is no longer in our assortment.

#### Features:

- Powerful hybrid effect spot, strobe and UV effect in one device
- Flat version requires minimal space when mounting
- 24 powerful LEDs SMD 5050 cold white (CW) (homogenous color mix)
- 1 powerful LED 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color macros adjustable; colors preset; program selection; color blend stepless; Dimmer electronic
- Strobe effect; UV effect
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- Flicker-free
- With a beam angle of 16°
- With double bracket
- Mains input and output for power linking up to 8 units Package contents
- 1 x remote control

#### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20

### Logistic

EAN / GTIN: 4026397603576 Weight: 2,44 kg Length: 0.30 m Width: 0.28 m Heigth: 0.16 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	24 x SMD 5050 cold white (CW) (homogenous color mix)
	1 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
	9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 6; 14; 26
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	
Beam angle (1/2 peak):	16°
	28°
Beam angle (1/10 peak):	39°
	54°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 28 cm
	Depth: 12,2 cm
	Height: 28,6 cm
Weight:	2,10 kg
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting