#### Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

# eurolite

## EUROLITE LED SLS-144 RGBW Floor

Flat spotlight with 144 LEDs in the colors red, green, blue and white

The article is no longer in our assortment.

#### Features:

- Static colors, RGBW color blend, internal programs, dimmer, strobe
- Master/slave function for synchronous operation with several devices
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Additional rubber feet when the spot shall be positioned on the floor without mounting bracket
- DMX and power terminals intelligently designed for easy wiring
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 144 powerful LEDs 5 mm R/G/B/W (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 10° Package contents
- 1 x device, 1 x power cord, 1 x remote control, 1 x user manual

### **Technical specifications:**

Power supply:

100-240 V AC, 50/60 Hz

#### Logistic

EAN / GTIN: 4026397555752 Weight: 1,34 kg Length: 0.26 m Width: 0.21 m Heigth: 0.13 m











GTIN: 4026397555752

Art. No.: 51915280

IP classification:   IP20     Protection class:   Protection class II     Power connection:   Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)     Cable length:   1.4 m     Power output:   1 x IEC connector (F) mounting version     Fuse:   5 x 20 mm, T 0.5 A fuse replaceable     Lamp type:   LED lamp     LED type:   144 x 5 mm R/G/BW (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX output:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light 'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR     DELUXE; Light Captain   Deam angle:     Beam angle:   10°     Beam angle:   10°     Beam angle:   10°     Beam angle:   20°     Housing color:   Black     Dimensions:   Width: 19 cm     Dep	Power consumption:	17 W
Power connection:   Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)     Cable length:   1,4 m     Power output:   1 x IEC connector (F) mounting version     Fuse:   5 x 20 mm, T 0,5 A fuse replaceable     Lamp type:   LED lamp     LED type:   144 x 5 mm R/G/B/W (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX output:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (M) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 444; LED EASY OPERATOR 444; LED EASY     Beam angle:   10°     Beam angle:   10°     Beam angle:   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control	IP classification:	IP20
version power supply cord with safety plug (provided)     Cable length:   1,4 m     Power output:   1 x IEC connector (F) mounting version     Fuse:   5 x 20 mm, T 0,5 A fuse replaceable     Lamp type:   LED lamp     LED type:   144 x 5 mm R/G/B/W (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX input:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Protection class:	Protection class II
Power output:   1 x IEC connector (F) mounting version     Fuse:   5 x 20 mm, T 0,5 A fuse replaceable     Lamp type:   LED lamp     LED type:   144 x 5 mm R/G/B/W (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX output:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR back; LED EASY OPERATOR beLUXE; Light Captain     Beam angle:   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm     Depth: 14 cm   Height: 21 cm     Weight:   1,12 kg     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Power connection:	version power supply cord with safety plug
Fuse:   5 x 20 mm, T 0,5 A fuse replaceable     Lamp type:   LED lamp     LED type:   144 x 5 mm R/G/B/W (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX output:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/12 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Cable length:	1,4 m
Lamp type:   LED lamp     LED type:   144 x 5 mm R/G/B/W (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX input:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/12 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Batery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Power output:	1 x IEC connector (F) mounting version
LED type:   144 x 5 mm R/G/B/W (homogenous color mix)     Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX output:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/12 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Battery:     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Specifications     Specifications   Not designed for household room illumination	Fuse:	5 x 20 mm, T 0,5 A fuse replaceable
Flash rate:   0 - 10 Hz     DMX channels:   6; 4     DMX input:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/12 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Lamp type:	LED lamp
DMX channels:   6; 4     DMX input:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light 'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm     Weight:   1,12 kg     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	LED type:	144 x 5 mm R/G/B/W (homogenous color mix)
DMX input:   1 x 3-pin XLR (M) mounting version     DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Battery:     1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Flash rate:	0 - 10 Hz
DMX output:   1 x 3-pin XLR (F) mounting version     Cooling:   Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   Image: 10°     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	DMX channels:	6; 4
Cooling fan     Cooling fan     Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   1x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:   Not designed for household room illumination	DMX input:	1 x 3-pin XLR (M) mounting version
Control:   Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   1x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	DMX output:	1 x 3-pin XLR (F) mounting version
IR remote control; master/slave function     Preprogrammed in:   Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Cooling:	Cooling fan
LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain     Beam angle:   10°     Beam angle (1/2 peak):   10°     Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm Depth: 14 cm Height: 21 cm     Weight:   1,12 kg     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Control:	
Beam angle (1/2 peak): 10°   Beam angle (1/10 peak): 20°   Housing color: Black   Dimensions: Width: 19 cm   Depth: 14 cm   Height: 21 cm   Weight: 1,12 kg   Remote control   Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in   Legal specifications   Special product: Not designed for household room illumination	Preprogrammed in:	LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR
Beam angle (1/10 peak):   20°     Housing color:   Black     Dimensions:   Width: 19 cm     Depth: 14 cm   Height: 21 cm     Weight:   1,12 kg     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Beam angle:	
Housing color:   Black     Dimensions:   Width: 19 cm     Depth: 14 cm   Height: 21 cm     Weight:   1,12 kg     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Beam angle (1/2 peak):	10°
Dimensions:   Width: 19 cm     Depth: 14 cm   Height: 21 cm     Weight:   1,12 kg     Remote control   1x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   Special product:	Beam angle (1/10 peak):	20°
Depth: 14 cm     Height: 21 cm     Weight:   1,12 kg     Remote control     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications     Special product:   Not designed for household room illumination	Housing color:	Black
Height: 21 cm     Weight:   1,12 kg     Remote control   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   5pecial product:     Not designed for household room illumination	Dimensions:	Width: 19 cm
Weight:   1,12 kg     Remote control   1     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications   5     Special product:   Not designed for household room illumination		•
Remote control     Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications     Special product:   Not designed for household room illumination		Height: 21 cm
Battery:   1 x button cell 3.0 V CR2025 lithium manganese built-in     Legal specifications     Special product:   Not designed for household room illumination	Weight:	1,12 kg
built-in   Legal specifications   Special product: Not designed for household room illumination	Remote control	
Special product: Not designed for household room illumination	Battery:	
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting