

EUROLITE LED SLS-30 COB UV Floor

Compact UV spotlight with 30 W LED, DMX and remote control

Art. No.: 51915303

GTIN: 4026397669305



Features:

- Striking blacklight effect
- Strobe effect with adjustable speed
- DMX and power terminals intelligently designed for easy wiring
- 1 LED 30 W COB (chip-on-board) ultra violet (UV)
- UV effect; strobe effect; wash effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light'J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 18°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397669305

Weight: 1,30 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 20 W

IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	IR remote control; DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	65°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Width: 21.5 cm Depth: 12.7 cm Height: 22.8 cm
Weight:	1.10 kg
Noise classification:	Class 3 (clearly perceptible sounds); class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm; 2 x Ø10mm
Material:	Metal, 1.5 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x battery

1 x user manual