

EUROLITE LED 4C-12 Silent Slim Spot

Silent 4in1 LED spotlight with RGBW color mixture

Art. No.: 51915316

GTIN: 4026397661583



List price: 296.31 €

incl. 19% VAT.

Features:

- Flat version requires minimal space when mounting
- 12 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone; QuickDMX via USB (optional); sound to light via microphone; master/slave function
- With a beam angle of 16°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Color blend stepless; Dimmer stepless
- Silent operation
- Strobe effect
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light' J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397661583

Weight: 4,00 kg

Length: 0.33 m

Width: 0.31 m

Height: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	12 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone; QuickDMX via USB (optional); sound to light via microphone; master/slave function
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light´J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	35°
Color temperature:	6500K
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display
Material:	Aluminum casting; metal
Dimensions:	Width: 28,5 cm Depth: 10,5 cm Height: 29,5 cm
Weight:	3,50 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Remote control	

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting