

EUROLITE LED SLS-7 HCL Floor

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

Art. No.: 51915379

GTIN: 4026397612912



Features:

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- 2 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Fixtures available for Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 17°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Available in various colors
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397612912

Weight: 1,63 kg

Length: 0.25 m

Width: 0.24 m

Height: 0.15 m

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 20 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Fuse: | 5 x 20 mm, T 0.5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 3; 4; 6; 10 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | 1 x cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control |
| Fixtures available for: | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° |
| Beam angle (1/10 peak): | 39° |
| Wavelength: | Ultra violet (UV) 400 nm |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | Monochrome 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |
| Material: | ABS Acrylonitrile butadiene styrene; metal |
| Dimensions: | Width: 22 cm Depth: 11 cm Height: 21 cm |
| Weight: | 1.38 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Cable construction: | 3 x 0.75 mm ² H05VV-F |
| Cable length: | Approx. 1.2 m |
| Diameter mounting holes: | 5 x Ø11mm |
| Material: | Metal, 2 mm |
| Color: | Black |

Battery:

1 x button cell 3.0 V CR2025 lithium manganese
built-in

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x user manual